

SHOP. CONNECT. ENJOY.



KAR PRODUCTS INC./DISTRIBUTOR -- 65376-ALL PURPOSE SILICONE LUBRICANT -- 6850-00N008186

=====  
Product Identification  
=====

Product ID:65376-ALL PURPOSE SILICONE LUBRICANT  
MSDS Date:01/01/1987  
FSC:6850  
NIIN:00N008186  
MSDS Number: BCPY  
=== Responsible Party ===  
Company Name:KAR PRODUCTS INC./DISTRIBUTOR  
Emergency Phone Num:312-296-6111  
CAGE:5L381  
=== Contractor Identification ===  
Company Name:KAR PRODUCTS  
Address:461 NORTH THIRD AVENUE  
Box:City:DES PLAINES  
State:IL  
ZIP:60016  
Country:US  
Phone:847-296-6111  
CAGE:5L381

=====  
Composition/Information on Ingredients  
=====

Ingred Name:DIMETHYL SILICONE  
  
Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)  
CAS:71-55-6  
RTECS #:KJ2975000  
Fraction by Wt: 70.0%  
OSHA PEL:350 PPM/450 STEL  
ACGIH TLV:350 PPM/450 STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS  
Ozone Depleting Chemical:1

Ingred Name:PROPANE  
CAS:74-98-6  
RTECS #:TX2275000  
Fraction by Wt: 17.0%  
OSHA PEL:1000 PPM  
ACGIH TLV:ASPHYXIAN; 9192

=====  
Hazards Identification  
=====

Effects of Overexposure:SKIN:DEFAT,RED,IRRIT,EFTS  
REVERSIBLE.INHAL:DIZZY,DIFFICULT BRTHG,VOMIT;IF HIGH CONC (SEE SUPP  
DATA)

=====  
First Aid Measures  
=====

First Aid:EYES:FLUSH IMMED W/LARGE AMTS OF H\*2O FOR @ LEAST 15 MIN.  
SKIN:WASH W/SOAP & H\*2O.INHAL:IF UNCONSCIOUS,REMOVE TO FRESH  
AIR,GIVE O\*2 & CALL DR. INGEST:DO NOT INDUCE VOMITING.GASTRIC  
LAVAGE.CALL DR.

=====  
Fire Fighting Measures  
=====

Flash Point:-40F (-40C), TCC  
Lower Limits:1.8  
Upper Limits:12.0  
Extinguishing Media:H\*2O FOG,DRY CHEMICAL/CO\*2  
Fire Fighting Procedures:USE PRESS DEMAND SCBA,FULL PROT CLTHG.KEEP  
(SEE SUPP DATA)  
Unusual Fire/Explosion Hazard:AT ELEVATED TEMP(> 130F) CNTNRS MAY  
VENT,BURST/RUPTURE.THERMAL DECOMP PROD MAY INCLUDE HCL,PHOSGENE.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:USE ABSORBENT SWEEPING COMPOUND TO SOAK UP  
MATERIAL.PUT INTO CONTAINER & DISPOSE OF AS HAZARDOUS WASTE.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS/OPEN  
FLM.STORE @ TEMP < 120F.DONT SMOKE WHILE SPRAYING.WASH HANDS AFTER  
USE.  
Other Precautions:NO SMOKING IN AREA.DONT USE IN GENL VICINITY OF ARC  
WELDING,OPEN FLM/HOT SURF.HEAT/UV RADIATION MAY CAUSE HCL,PHOSGENE  
FORMATION. VAP PRESS:42 PSIG @ 70F. DOP:9-25-86.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NIOSH/MSHA APPROVED SCBA IF TLV LIMIT IS BEING  
EXCEEDED.  
Ventilation:LOCAL EXHAUST VENTILATION  
Protective Gloves:NOT IF SPRAYING  
Eye Protection:SFTY GLASSES/CHEM GOGGLES  
Other Protective Equipment:LONG SLEEVES & LONG PANTS  
Supplemental Safety and Health  
SPECIAL FIRE PROC:CNTRNS COOL.USE EQUIP/SHIELD TO PROT FROM BURST/VENT  
CNTRNS.OVEREXP EFTS:POSS NARCOSIS.LONG TERM EXP (YEARS) POSS  
LUNG,LIVER/KIDNEY DAMAGE.HEART DISEASE AGGRAVATED BY EXP.

=====  
Physical/Chemical Properties  
=====

Boiling Pt:B.P. Text:-40 TO 194F  
Vapor Density:4.0  
Spec Gravity:1.2  
Evaporation Rate & Reference:6.0 (BUTYL AC)  
Solubility in Water:NONE  
Appearance and Odor:CLEAR APPEARANCE;SOLVENT ODOR.

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES  
NONE  
Stability Condition to Avoid:HIGH TEMPERATURES  
Hazardous Decomposition Products:IN FIRE FORMS PHOSGENE & HCL.

=====  
Disposal Considerations  
=====

Waste Disposal Methods:DISPOSE OF AS HAZARDOUS WASTE IAW LOCAL,STATE &  
FEDERAL (EPA RCRA) REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.