



SAFETY DATA SHEET

Issuing Date 20-Nov-2013

Revision Date 20-Nov-2013

Revision Number 0

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Lock-Ease

Other means of identification

Product Code(s) LE-4, LE-4BK, LEC-4, LEK-4, LEK-4C

UN-Number UN1268

Synonyms Graphited Lock Fluid

Recommended use of the chemical and restrictions on use

Recommended Use All types of locks, household appliances, tools, guns, reels and other mechanisms.

Uses advised against No information available

Supplier's details

Supplier Address

AGS Company
P.O. Box 729
Muskegon, MI
49443
TEL: 800-253-0403

Emergency telephone number

Emergency Telephone Number 800-255-3924

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1B
Aspiration Toxicity	Category 1
Flammable liquids	Category 3

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word**Danger****Hazard Statements**

- May cause genetic defects
- May cause cancer
- May be fatal if swallowed and enters airways
-
- Flammable liquid and vapor.

**Appearance** Dark gray**Physical State** Liquid.**Odor** Solvent**Precautionary Statements****Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Keep away from heat/sparks/open flames/hot surfaces - No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ventilating/lighting/equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge.

General Advice

- If exposed or concerned: Get medical attention/advice

Skin

- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Ingestion

- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
- Do NOT induce vomiting.

Fire

- In case of fire: Use CO2, dry chemical, or foam for extinction.

Storage

- Store locked up
- Store in a well-ventilated place. Keep cool.

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Synonyms**

Graphited Lock Fluid

Chemical Name	CAS-No	Weight %	Trade secret
Stoddard solvent	8052-41-3	60-100	*
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	7-13	*
Graphite	7782-42-5	0.1-1	*
Ethylbenzene	100-41-4	<0.2	*

**The exact percentage (concentration) of composition has been withheld as a trade secret.*

4. FIRST AID MEASURES**Description of necessary first-aid measures**

Eye Contact Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing. Get medical attention if irritation persists.

Skin Contact Take off contaminated clothing and wash before reuse.

Inhalation Move to fresh air in case of accidental inhalation of vapors.

Ingestion Call a physician or Poison Control Center immediately. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects No information available.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Aspiration hazard.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Use: Carbon dioxide (CO₂). Dry chemical. Foam. Water spray.

Unsuitable Extinguishing Media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Flammable. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Explosion Data

Sensitivity to Mechanical Impact

None.

Sensitivity to Static Discharge

Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures****Personal Precautions**

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded.

Environmental Precautions

Environmental Precautions Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. See Section 12 for additional Ecological Information

Methods and materials for containment and cleaning up

Methods for Containment A vapor suppressing foam may be used to reduce vapors.

Methods for Cleaning Up Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Non-sparking tools should be used. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Use only in an area containing flame proof equipment. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid breathing vapors. Remove and wash contaminated clothing before re-use.

Conditions for safe storage, including any incompatibilities

Storage Keep away from open flames, hot surfaces and sources of ignition. Keep container tightly closed in a dry and well-ventilated place.

Incompatible Products Strong acids. Strong bases. Strong oxidizing agents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
Graphite 7782-42-5	-	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ total dust synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ respirable dust
Aluminum iso-propoxide 555-31-7	TWA: 1 mg/m ³ respirable fraction	-	-
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³

Naphthalene 91-20-3	STEL: 15 ppm TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³
Calcium hydroxide 1305-62-0	TWA: 5 mg/m ³	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ not in effect as a result of reconsideration	TWA: 5 mg/m ³
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
Benzene 71-43-2	STEL = 2.5 ppm TWA: 0.5 ppm S*	TWA: 1 ppm TWA: 10 ppm (vacated) TWA: 10 ppm (vacated) STEL: 50 ppm (vacated) Ceiling: 25 ppm Ceiling: 25 ppm STEL: 5 ppm	IDLH: 500 ppm TWA: 0.1 ppm STEL: 1 ppm

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health.

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Measures

Showers. Eyewash stations. Explosion proof ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Safety glasses with side-shields.

Skin and Body Protection

Wear protective gloves/clothing.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures

Do not eat, drink or smoke when using this product. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	Appearance	Dark gray
Odor	Solvent	Odor Threshold	No information available
Property	Values	Remarks/ - Method	
pH	No data available	None known	
Melting Point/Range	No data available	None known	
Boiling Point/Boiling Range	156-197 °C / 312-387 °F	None known	
Flash Point	38 °C / 101 °F	None known	
Evaporation rate	Slower than Butyl Acetate	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limits in Air			
upper flammability limit	No data available		
lower flammability limit	No data available		
Vapor Pressure	1-5	None known	

Vapor Density	Heavier than air	Air = 1
Relative Density	No data available	None known
Specific Gravity	0.7963	None known
Water Solubility	Negligible	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	No data available	None known

Flammable Properties Not flammable

Explosive Properties No data available

Oxidizing Properties No data available

Other information

VOC Content (%) No data available

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	May cause irritation of respiratory tract.
Eye Contact	May cause slight irritation.
Skin Contact	May cause irritation.
Ingestion	May be fatal if swallowed and enters airways.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethylbenzene	= 3500 mg/kg (Rat)	= 15354 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization No information available.
Mutagenic Effects May cause genetic defects.
Carcinogenicity The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Petroleum distillates, hydrotreated heavy naphthenic	A2	Group 1		X
Ethylbenzene	A3	Group 2B	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Reproductive Toxicity No information available.
STOT - single exposure No information available.
STOT - repeated exposure No information available.
Aspiration Hazard May be fatal if swallowed and enters airways

Numerical measures of toxicity - Product

Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION**Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Petroleum distillates, hydrotreated heavy naphthenic 64742-52-5		LC50 96 h: > 5000 mg/L (Oncorhynchus mykiss)		EC50 48 h: > 1000 mg/L (Daphnia magna)
Palmitic acid 57-10-3		LC50 96 h: = 150 mg/L (Oryzias latipes)		
Ethylbenzene 100-41-4	EC50 72 h: = 4.6 mg/L (Pseudokirchneriella subcapitata) EC50 96 h: > 438 mg/L (Pseudokirchneriella subcapitata) EC50 72 h: 2.6 - 11.3 mg/L static (Pseudokirchneriella subcapitata) EC50 96 h: 1.7 - 7.6 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: = 11 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: 11.0 - 18.0 mg/L static (Oncorhynchus mykiss) LC50 96 h: = 4.2 mg/L semi-static (Oncorhynchus mykiss) LC50 96 h: 7.55 - 11 mg/L flow-through (Pimephales promelas) LC50 96 h: = 32 mg/L static (Lepomis macrochirus) LC50 96 h: 9.1 - 15.6 mg/L static (Pimephales promelas) LC50 96 h: = 9.6 mg/L static (Poecilia reticulata)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50 48 h: 1.8 - 2.4 mg/L (Daphnia magna)
Benzoic acid 65-85-0	EC50 3 h: = 5 mg/L (Anabaena inaequalis)	LC50 96 h: = 180 mg/L (Gambusia affinis)		EC50 24 h: = 300 mg/L (Daphnia magna) EC50 48 h: = 860 mg/L Static (Daphnia magna)

Naphthalene 91-20-3	EC50 72 h: = 0.4 mg/L (Skeletonema costatum)	LC50 96 h: 0.91-2.82 mg/L static (Oncorhynchus mykiss) LC50 96 h: 5.74-6.44 mg/L flow-through (Pimephales promelas) LC50 96 h: = 1.6 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: = 1.99 mg/L static (Pimephales promelas) LC50 96 h: = 31.0265 mg/L static (Lepomis macrochirus)	EC50 = 0.93 mg/L 30 min EC50 > 20 mg/L 18 h	EC50 48 h: 1.09 - 3.4 mg/L Static (Daphnia magna) EC50 48 h: = 1.96 mg/L Flow through (Daphnia magna) LC50 48 h: = 2.16 mg/L (Daphnia magna)
Myristic acid 544-63-8		LC50 96 h: = 118 mg/L static (Oryzias latipes)		EC50 16 h: > 27 mg/L (Artemia salina)
Petroleum distillates, hydrotreated middle 64742-46-7		LC50: 35 mg/L Pimephales promelas 96 h flow-through LC50: >10000 mg/L Pimephales promelas 96 h static		
Calcium hydroxide 1305-62-0		LC50 96 h: = 160 mg/L static (Gambusia affinis)		
Toluene 108-88-3	EC50: >433 mg/L Pseudokirchneriella subcapitata 96 h EC50: 12.5 mg/L Pseudokirchneriella subcapitata 72 h static	LC50: 15.22-19.05 mg/L Pimephales promelas 96 h flow-through LC50: 12.6 mg/L Pimephales promelas 96 h static LC50: 5.89-7.81 mg/L Oncorhynchus mykiss 96 h flow-through LC50: 14.1-17.16 mg/L Oncorhynchus mykiss 96 h static LC50: 5.8 mg/L Oncorhynchus mykiss 96 h semi-static LC50: 11.0-15.0 mg/L Lepomis macrochirus 96 h static LC50: 54 mg/L Oryzias latipes 96 h static LC50: 28.2 mg/L Poecilia reticulata 96 h semi-static LC50: 50.87-70.34 mg/L Poecilia reticulata 96 h static	EC50 = 19.7 mg/L 30 min	EC50 48 h: 5.46 - 9.83 mg/L Static (Daphnia magna) EC50 48 h: = 11.5 mg/L (Daphnia magna)
Benzene 71-43-2	EC50 72 h: = 29 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: 10.7-14.7 mg/L flow-through (Pimephales promelas) LC50 96 h: 22330-41160 µg/L static (Pimephales promelas) LC50 96 h: 70000-142000 µg/L static (Lepomis macrochirus) LC50 96 h: = 22.49 mg/L static (Lepomis macrochirus) LC50 96 h: = 28.6 mg/L static (Poecilia reticulata) LC50 96 h: = 5.3 mg/L flow-through (Oncorhynchus mykiss)		EC50 48 h: 8.76 - 15.6 mg/L Static (Daphnia magna) EC50 48 h: = 10 mg/L (Daphnia magna)

Persistence and Degradability No information available.

Bioaccumulation No information available.

Chemical Name	Log Pow
Ethylbenzene	3.118

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

US EPA Waste Number D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Ethylbenzene - 100-41-4		Included in waste stream: F039		
Naphthalene - 91-20-3	U165	Included in waste streams: F024, F025, F034, F039, K001, K035, K060, K087, K145		U165
Toluene - 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220
Benzene - 71-43-2	waste number U019	Included in waste streams: F005, F024, F025, F037, F038, F039, K085, K104, K105, K141, K142, K143, K144, K145, K147, K151, K159, K169, K171, K172	= 0.5 mg/L regulatory level	U019

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Ethylbenzene	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN-Number UN1268
Proper shipping name Petroleum distillates, n.o.s.
Hazard Class 3
Packing Group III
Description UN1268, Petroleum distillates, n.o.s. (Stoddard Solvent), 3, III
Emergency Response Guide Number 128

TDG

UN-Number UN1268
Proper Shipping Name Petroleum distillates, n.o.s.
Hazard Class 3
Packing Group III
Description UN1268, Petroleum distillates, n.o.s. (Stoddard Solvent), 3, III

UN-Number UN1268
Proper Shipping Name Petroleum distillates, n.o.s.
Hazard Class 3
Packing Group III
Description UN1268, Petroleum distillates, n.o.s.(Stoddard Solvent), 3, III

ICAO

UN-Number UN1268

Proper shipping name	Petroleum distillates, n.o.s.
Hazard Class	3
Packing Group	III
Description	UN1268, Petroleum distillates, n.o.s.(Stoddard Solvent), 3, III

IATA

UN-Number	UN1268
Proper Shipping Name	Petroleum distillates, n.o.s.
Hazard Class	3
Packing Group	III
ERG Code	3L
Description	UN1268, Petroleum distillates, n.o.s.(Stoddard Solvent), 3, III

IMDG/IMO

UN-Number	UN1268
Proper Shipping Name	Petroleum distillates, n.o.s.
Hazard Class	3
Packing Group	III
EmS No.	F-E, S-E
Description	UN1268, Petroleum distillates, n.o.s., 3, III, (38°C c.c.)

UN-Number	UN1268
Proper Shipping Name	Petroleum distillates, n.o.s.
Hazard Class	3
Packing Group	III
Classification Code	F1
Description	UN1268, Petroleum distillates, n.o.s.(Stoddard Solvent), 3, III

ADR

UN-Number	UN1268
Proper Shipping Name	Petroleum distillates, n.o.s.
Hazard Class	3
Packing Group	III
Classification Code	F1
Tunnel Restriction Code	(D/E)
Description	UN1268, Petroleum distillates, n.o.s.(Stoddard Solvent), 3, III, (D/E)
ADR/RID-Labels	3
Proper Shipping Name	Petroleum distillates, n.o.s.
Hazard Class	3
Packing Group	III
Classification Code	F1
Special Provisions	363
Description	UN1268, Petroleum distillates, n.o.s.(Stoddard Solvent), 3, III
Limited Quantity	5 L
Ventilation	VE01

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Ethylbenzene	100-41-4	<0.2	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ethylbenzene	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ethylbenzene	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Ethylbenzene	100-41-4	Carcinogen
Naphthalene	91-20-3	Carcinogen
Toluene	108-88-3	Developmental
Benzene	71-43-2	Carcinogen Developmental Male Reproductive

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Stoddard solvent	X	X	X		X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA	Health Hazard 1	Flammability 2	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazard 1*	Flammability 2	Physical Hazard 0	Personal Protection X

Prepared By

Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date

20-Nov-2013

Revision Date

20-Nov-2013

Revision Note

Initial Release.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet