



# Material Safety Data Sheet

## Section 1: Product & Company Identification

Product Name: NAPA/CRC® Heavy Duty Silicone™ (CA & OTC)

Product Number (s): 091422

**Manufactured By:**

CRC Industries, Inc.  
885 Louis Drive  
Warminster, PA 18974  
[www.crcindustries.com](http://www.crcindustries.com)

|                            |                |
|----------------------------|----------------|
| General Information        | (215) 674-4300 |
| Technical Assistance       | (800) 521-3168 |
| Customer Service           | (800) 272-8963 |
| 24-Hr Emergency (CHEMTREC) | (800) 424-9300 |

## Section 2: Hazards Identification

### Emergency Overview

Appearance & Odor: Clear water-white liquid, solvent odor

### DANGER

Extremely Flammable. Harmful or Fatal if Swallowed. Eye and Skin Irritant. Contents Under Pressure.

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

### Potential Health Effects:

|                  |                                                                                                                                                                                                                                                       |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EYE:             | Eye irritant. Contact may cause moderate to severe eye irritation including stinging, watering and redness.                                                                                                                                           |
| SKIN:            | Skin irritant. Contact may cause redness, itching, burning, and skin damage. Prolonged or repeated contact can worsen irritation by causing drying and cracking of the skin, leading to dermatitis (inflammation).                                    |
| INHALATION:      | Low to moderate degree of toxicity by inhalation. Effects of overexposure may include irritation to the respiratory tract and signs of nervous system depression (headache, drowsiness, dizziness, loss of coordination, disorientation and fatigue). |
| INGESTION:       | Main hazard is aspiration. This material can enter lungs during swallowing or vomiting and cause lung inflammation and damage. Swallowing this material may also cause nausea and diarrhea. Acetone poisoning may result in liver and kidney damage.  |
| CHRONIC EFFECTS: | Exposure to high concentrations of this material may increase the sensitivity of the heart to certain drugs. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.                  |
| TARGET ORGANS:   | Liver, kidney, central nervous system.                                                                                                                                                                                                                |

Medical Conditions Aggravated by Exposure: skin disorders, respiratory (asthma-like) disorders

See Section 11 for toxicology and carcinogenicity information on product ingredients.

---

### Section 3: Composition/Information on Ingredients

| COMPONENT               | CAS NUMBER | % by Wt. |
|-------------------------|------------|----------|
| Heptane isomers         | various    | 25 - 35  |
| Acetone                 | 67-64-1    | 30 - 40  |
| Polydimethylsiloxane    | 63148-62-9 | 2 - 5    |
| Liquefied petroleum gas | 68476-86-8 | 25 - 35  |

---

### Section 4: First Aid Measures

**Eye Contact:** Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

**Skin Contact:** Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.

**Inhalation:** Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.

**Ingestion:** Do NOT induce vomiting or give anything by mouth because material can enter the lungs and cause severe lung damage. Seek medical attention immediately.

**Note to Physicians:** Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to high concentrations of hydrocarbon solvents. The use of other drugs with less arrhythmogenic potential should be considered.

---

### Section 5: Fire-Fighting Measures

**Flammable Properties:** This product is extremely flammable in accordance with aerosol flammability definitions (16 CFR 1500.3(c)(6)).

|                           |             |                        |      |
|---------------------------|-------------|------------------------|------|
| Flash Point:              | < 0 F (TCC) | Upper Explosive Limit: | 12.8 |
| Autoignition Temperature: | ND          | Lower Explosive Limit: | 2.5  |

**Suitable Extinguishing Media:** Dry chemical, carbon dioxide or foam is recommended.

**Products of Combustion:** Oxides of carbon; thermal decomposition may generate silicon dioxide and formaldehyde

**Protection of Fire-Fighters:** Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition. Avoid spreading burning liquid with water used for cooling purposes.

---

### Section 6: Accidental Release Measures

**Personal Precautions:** Use personal protection recommended in Section 8.

**Product Name: NAPA/CRC®Heavy Duty Silicone™ (CA & OTC) Product Number (s): 091422**

**Environmental Precautions:** Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

**Methods for Containment & Clean-up:** Eliminate all potential sources of ignition. Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

---

**Section 7: Handling and Storage**

**Handling Procedures:** Do not use on or around any potential sources of ignition or live equipment. Do not touch container to electrical sources as container will conduct electricity. Wash thoroughly after use and before handling food.

**Storage Procedures:** Aerosol cans must be maintained below 120 F to prevent cans from rupturing. Use and store this material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Keep away from incompatible material.

**Aerosol Storage Level:** III

---

**Section 8: Exposure Controls/Personal Protection**

**Exposure Guidelines:**

| COMPONENT                                                     | OSHA    |          | ACGIH |      | OTHER |        | UNIT |
|---------------------------------------------------------------|---------|----------|-------|------|-------|--------|------|
|                                                               | TWA     | STEL     | TWA   | STEL | TWA   | SOURCE |      |
| Heptane isomers                                               | 500     | NE       | 400   | 500  | NE    |        | ppm  |
| Acetone                                                       | 750 (v) | 1000 (v) | 500   | 750  | NE    |        | ppm  |
| Polydimethylsiloxane                                          | NE      | NE       | NE    | NE   | NE    |        |      |
| Liquefied petroleum gas                                       | 1000    | NE       | 1000  | NE   | NE    |        | ppm  |
| N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated |         |          |       |      |       |        |      |

**Engineering Controls:** Area should have ventilation to provide fresh air. Use local exhaust to prevent accumulation of vapors. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations

**Respiratory Protection:** None required for normal work where adequate ventilation is provided. Use a NIOSH-approved cartridge respirator with an organic vapor cartridge if vapors exceed exposure limits. Use a self-contained breathing apparatus in confined spaces and for emergencies.

**Eye/face Protection:** For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

**Skin Protection:** Use protective gloves such as nitrile, PVA or Viton®. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

---

**Section 9: Physical and Chemical Properties**

**Physical State:** liquid

**Color:** clear, water-white

**Product Name:** NAPA/CRC®Heavy Duty Silicone™ (CA & OTC) **Product Number (s):** 091422

Odor: solvent  
Specific Gravity: 0.748  
Initial Boiling Point: 132 F  
Freezing Point: ND  
Vapor Pressure: ND  
Vapor Density: > 1 (air = 1)  
Evaporation Rate: > 1 (butyl acetate = 1)  
Solubility: slightly soluble in water  
pH: NA  
Volatile Organic Compounds: wt %: 59.5 g/L: 445.1 lbs./gal: 3.7

---

## Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Sources of ignition, temperature extremes

Incompatible Materials: Avoid contact with acids and oxidizers such as chlorine and other halogens, chromates, perchlorates, peroxides and oxygen.

Hazardous Decomposition Products: oxides of carbon

Possibility of Hazardous Reactions: No

---

## Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

### ACUTE EFFECTS

| <u>Component</u> | <u>Test</u> | <u>Result</u>            | <u>Route</u> | <u>Species</u> |
|------------------|-------------|--------------------------|--------------|----------------|
| n-heptane        | LD50        | 103 g/m <sup>3</sup> /4H | Inhalation   | Rat            |
| acetone          | LD50        | 76 mg/L/4H               | Inhalation   | Rat            |
| acetone          | LD50        | 1800 mg/kg               | Oral         | Rat            |
| n-heptane        | LD50        | > 15 g/kg                | Oral         | Mouse          |

### CHRONIC EFFECTS

Carcinogenicity:

|       | <u>Component</u> | <u>Result</u> |
|-------|------------------|---------------|
| OSHA: | none listed      |               |
| IARC: | none listed      |               |
| NTP:  | none listed      |               |

Mutagenicity: no information available

Other: none

---

## Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

**Product Name:** NAPA/CRC®Heavy Duty Silicone™ (CA & OTC) **Product Number (s):** 091422

Ecotoxicity: n-heptane - 24 Hr EC50 Daphnia magna: >10 mg/L  
acetone - 48 Hr EC50 Daphnia magna: 12600 mg/L  
Persistence / Degradability: No information available  
Bioaccumulation / Accumulation: No information available  
Mobility in Environment: No information available

---

### Section 13: Disposal Considerations

Disposal: The dispensed liquid product is a RCRA hazardous waste for the characteristic of ignitability with the following potential waste codes: D001. (See 40 CFR Part 261.20 – 261.33)  
Aerosol containers should be emptied and depressurized before disposal. Empty containers may be recycled. Any liquid product should be managed as a hazardous waste.

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

---

### Section 14: Transport Information

Proper shipping description:

US DOT (ground): Consumer Commodity, ORM-D

Special Provisions: None

---

### Section 15: Regulatory Information

#### U.S. Federal

#### Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

#### Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: Acetone (5000 lbs)

**Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.**

#### Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

|                                    |                       |     |
|------------------------------------|-----------------------|-----|
| Section 311/312 Hazard Categories: | Fire Hazard           | Yes |
|                                    | Reactive Hazard       | No  |
|                                    | Release of Pressure   | Yes |
|                                    | Acute Health Hazard   | Yes |
|                                    | Chronic Health Hazard | Yes |

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:  
None

#### Clean Air Act:

**Product Name: NAPA/CRC®Heavy Duty Silicone™ (CA & OTC) Product Number (s): 091422**

Section 112 Hazardous Air Pollutants (HAPs): None

**State Regulations**

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: toluene (0.005%)

State Right to Know:

New Jersey: 142-82-5, 110-82-7, 67-64-1, 68476-86-8  
Pennsylvania: 142-82-5, 110-82-7, 67-64-1, 68476-86-8  
Massachusetts: 142-82-5, 110-82-7, 67-64-1, 68476-86-8  
Rhode Island : 142-82-5, 110-82-7, 67-64-1, 68476-86-8

**Additional Regulatory Information:** This product complies with Consumer Product VOC regulations as a Silicone-based Multi-Purpose Lubricant.

---

**Section 16: Other Information**

|       |           |                 |               |        |
|-------|-----------|-----------------|---------------|--------|
| NFPA: | Health: 2 | Flammability: 3 | Reactivity: 0 |        |
| HMIS: | Health: 2 | Flammability: 3 | Reactivity: 0 | PPE: B |

Prepared By: Michelle Rudnick  
CRC #: 519C  
Revision Date: 11/21/2006

Changes since last revision: Section 13 revised.

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

|       |                                                           |           |                           |
|-------|-----------------------------------------------------------|-----------|---------------------------|
| CAS:  | Chemical Abstract Service                                 | NA:       | Not Applicable            |
| ppm:  | Parts per Million                                         | ND:       | Not Determined            |
| TCC:  | Tag Closed Cup                                            | NE:       | Not Established           |
| PMCC: | Pensky-Martens Closed Cup                                 | g/L:      | grams per Liter           |
| PPE:  | Personal Protection Equipment                             | lbs./gal: | pounds per gallon         |
| TWA:  | Time Weighted Average                                     | STEL:     | Short Term Exposure Limit |
| OSHA: | Occupational Safety and Health Administration             |           |                           |
| ACGIH | American Conference of Governmental Industrial Hygienists |           |                           |
| NIOSH | National Institute of Occupational Safety & Health        |           |                           |